

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) A method comprising:
allocating space in a host memory for use as a buffer;
copying contents of a memory of a network interface controller into the buffer;
modifying the contents of the network interface controller memory and correspondingly
modifying the contents of the buffer; and
accessing the contents of the buffer in response to a request for information in the
network interface controller memory.
2. (Canceled)
3. (Original) The method according to claim 1 further comprising: initializing a device
driver in a Network Driver Interface Specification environment to allocate the space in the host
memory in less than a second.
4. (Original) The method according to claim 3 comprising:
initializing the buffer to store the contents of the network interface controller memory
wherein initializing the buffer occurs at a different time from the driver initialization.
5. (Original) The method according to claim 1 comprising:
initializing a physical layer; and
subsequently initializing the buffer to store the contents of the network interface
controller memory.

6. (Original) The method according to claim 1 wherein the network interface controller memory comprises an EEPROM.

7. (Currently amended) A method comprising:
copying contents of a network interface controller memory into a buffer in host memory;
recopying the contents of the network interface controller memory into the buffer if the contents of the network interface controller memory are modified; and
accessing the contents of the buffer in response to a request for information in the network interface controller memory.

8. (Original) The method according to claim 7 further comprising:
initializing a driver to allocate memory space to the buffer.

9. (Original) The method according to claim 8 further comprising:
initializing the driver in a Network Driver Interface Specification environment in less than a second.

10. (Original) The method according to claim 8 further comprising:
initializing the buffer at a time different from the driver initialization.

11. (Original) The method according to claim 7 further comprising:
initializing the buffer to store the contents of the network interface controller memory in response to a first request to read the contents of the network interface controller memory.

12. (Currently amended) An apparatus comprising:
a network interface controller containing a memory;
a bus coupled to the controller;

a host memory coupled to the bus and having space allocated for use as a buffer; and
a processor coupled to the host memory and configured to:
copy contents of the network interface controller memory into the buffer;
modify the contents of the network interface controller memory and correspondingly
modify the contents of the buffer; and
access the contents of the buffer in response to a request for information in the network
interface controller memory.

13. (Canceled)

14. (Original) The apparatus according to claim 12 wherein the processor is further
configured to:

initialize a device driver in a Network Driver Interface Specification environment to
allocate the space in the host memory in less than a second.

15. (Original) The apparatus according to claim 14 wherein the processor is further
configured to:

initialize the buffer to store the contents of the network interface controller memory,
wherein the buffer initialization occurs at a different time from the driver initialization.

16. (Original) The apparatus according to claim 12 wherein the processor is further
configured to:

initialize a physical layer; and
subsequently initialize the buffer to store the contents of the network interface controller
memory.

17. (Original) The apparatus according to claim 12 wherein the network interface
controller memory comprises an EEPROM.

18. (Currently amended) An apparatus comprising:
a network interface controller containing a memory;
a bus coupled to the controller;
a host memory coupled to the bus; and
a processor coupled to the host memory; wherein the processor is configured to:
copy contents of the network interface controller memory into a buffer in the host
memory;
access the contents of the buffer in response to a request for information in the
network interface controller memory; and
recopy the contents of the network interface controller memory into the buffer if
the contents of the network interface controller memory are modified.

19. (Original) The apparatus according to claim 18 wherein the processor is further
configured to:

initialize a driver in a network driver interface specification environment to allocate
memory space to the buffer in less than a second.

20. (Original) The apparatus according to claim 19 wherein the buffer is initialized at a
time different from the driver initialization.

21. (Original) The apparatus according to claim 18 wherein the processor is further
configured to:

initialize the buffer to store the contents of the network interface controller memory in
response to a first request to read the contents of the network interface controller memory.

22. (Currently amended) An article comprising a computer-readable medium that stores
computer-executable instructions for causing a computer system to:

allocate space in a host memory for use as a buffer;
copy contents of a memory of a network interface controller into the buffer;
modify the contents of the network interface controller memory and correspondingly
modify the contents of the buffer; and
access the contents of the buffer in response to a request for information in the network
interface controller memory.

23. (Canceled)

24. (Original) The article according to claim 22 further including instruction for causing
the computer system to:

initialize a device driver in a network driver interface specification environment to
allocate the space in the host memory in less than a second.

25. (Original) The article according to claim 24 further including instruction for causing
the computer system to:

initialize the buffer to store the contents of the network interface controller memory
wherein initializing the buffer occurs at a different time from the driver initialization.

26. (Original) The article according to claim 22 further including instructions for
causing the computer system to:

initialize a physical layer; and
subsequently initialize the buffer to store the contents of the network interface controller
memory.

27. (Currently amended) An article comprising a computer-readable medium that stores
computer-executable instructions for causing a computer system to:

copy contents of a network interface controller memory into a buffer in host memory;

recopy the contents of the network interface controller memory into the buffer if the contents of the network interface controller memory are modified; and

access the contents of the buffer in response to a request for information in the network interface controller memory.

28. (Original) The article according to claim 27 further including instructions for causing the computer system to:

initialize a driver in a Network Driver Interface Specification environment to allocate memory space to the buffer in less than a second.

29. (Original) The article according to claim 27 further including instructions for the computer system to:

initialize the buffer to store the contents of the network interface controller memory in response to a first request to read the contents of the network interface controller memory.

30. (Previously presented) The method according to claim 1 wherein correspondingly modifying the contents of the buffer occurs independently of a request by a host to access information in the network interface controller memory.

31. (Previously presented) The apparatus according to claim 12 wherein the contents of the buffer are correspondingly modified independently of a request by a host to access information in the memory of the network interface controller.

32. (Previously presented) The article according to claim 22 wherein the contents of the buffer are correspondingly modified independently of a request by a host to access information in the memory of the network interface controller.